



Providing Solutions in Pressure Sensitive Films

Product Construction Sheet

FLEXmount® TT 200 L-606 55 LA K

GENERAL DESCRIPTION:

This is a 2.0 mil (51 micron) permanent pressure sensitive acrylic adhesive supported with a semi bleached kraft differential release liner.

NOTE:

For all testing, transfer tape was laminated to 2.0 mil (51 micron) clear polyester (PM 200 CLEAR) film. Use with plasticized vinyl surface is not recommended.

UL RECOGNITION:

This product is UL recognized. For further information, please contact your FLEXcon Representative or reference FLEXcon's UL file No PGGU2.MH10170.

Table with 3 columns: PRODUCT DATA, VALUE, TEST METHOD. Row: Thickness mil (micron) Adhesive: 1.9-2.1 (48-53) +/- 0.1 (3) ASTM D 3652; Liner: 3.2 (81) +/- 10 %

ADHESION PROPERTIES\*\*

Table with 3 columns: Adhesion from, Average oz/in (N/m), TEST METHOD. Rows: Stainless Steel, Acrylic, Glass, Polypropylene\*\*\*; Expected Shear (hours); Tack (gm)

\*\* For guidance only, not to be used for setting specifications. Due to the custom nature of this product, the data presented are based on three or less production runs. \*\*\* Zippy adhesion.

Table with 2 columns: PROPERTY, VALUE. Rows: EXPECTED EXTERIOR LIFE, SERVICE TEMPERATURE, MINIMUM APPLICATION TEMPERATURE, STORAGE STABILITY

\* FLEXmount is a registered trademark of FLEXcon Company, Inc. 07/05/2006

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product.