



Providing Solutions in Pressure Sensitive Films

Product Construction Sheet

FLEXmount® TT 200 V-402 84 LA PFT

GENERAL DESCRIPTION:

This is a 2.0 mil (51 micron) high performance permanent pressure sensitive acrylic adhesive supported with a two-side poly coated natural kraft differential release liner.

NOTE:

For all testing, transfer tape was laminated to 2.0 mil (51 micron) clear polyester (PM 200 CLEAR) film.

Table with 3 columns: PRODUCT DATA, VALUE, TEST METHOD. Row: PHYSICAL PROPERTIES, Thickness mil (micron), Adhesive: 1.9-2.1 (48-53) +/- 0.2 (5), Liner: 6.4 (163) +/- 10 %, ASTM D 3652

ADHESION PROPERTIES\*\*

Table with 3 columns: Adhesion from, Average oz/in (N/m), TEST METHOD. Rows: Stainless Steel, Acrylic, Glass, Polypropylene, Expected Shear (hours), Tack (gm)

\*\* For guidance only, not to be used for setting specifications. Due to the custom nature of this product, the data presented are based on three or less production runs.

Table with 2 columns: PROPERTY, VALUE. Rows: EXPECTED EXTERIOR LIFE, SERVICE TEMPERATURE, MINIMUM APPLICATION TEMPERATURE, STORAGE STABILITY

\* FLEXmount is a registered trademark of FLEXcon Company, Inc. 06/19/2006

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product.