



### Benefits

- Excellent layflat release liner properties for printing and converting

### Features

- 2.0 mil clear polyester provides excellent clarity for exterior- or interior-mount window applications
- Printable via UV screen and UV inkjet
- Permanent pressure-sensitive acrylic adhesive bonds well to a variety of surfaces including chrome-coated metal, chrome-coated plastic, glass, auto glass and painted plastic
- Adhesive resists oozing and reduces adhesive build-up for ease of diecutting
- 90 lb. moisture stable polycoated layflat release liner ideal for sheet and roll-to-sheet converting
- Ideal for manual dispensing

### Additional Details

End-Use Applications: Parking Stickers Oil Change Stickers College/Alumni Decals After-market Decals

### Technical Data

#### Physical Properties

| Thickness (Mils [microns]) | Mils | Microns |
|----------------------------|------|---------|
| Total Product              | 9.92 |         |

Test Method:

Adhesion Properties

|                    |               |       |
|--------------------|---------------|-------|
| Ultimate Peel from | Average Oz/In | (N/m) |
|--------------------|---------------|-------|

Test Method:

|                                 |       |             |
|---------------------------------|-------|-------------|
| Additional Properties           | Value | Test Method |
| Expected Shear (hours)          |       |             |
| Tack (g)                        |       |             |
| Expected Exterior Life          |       |             |
| Additional Information          |       |             |
| Service Temperature             |       |             |
| Minimum Application Temperature |       |             |
| Storage Stability               |       |             |

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.