

Benefits

- Rich embossed, velvet-texture finish offers good resistance to scratches and fingerprints

Features

- 6.2 mil velvet-embossed rigid clear vinyl is a durable printable substrate
- Non-adhesive coated, primed vinyl (on the smooth underside) provides excellent ink adhesion for reverse printability via UV offset, UV and solvent screen, and UV and solvent inkjet (wide format)

Additional Details

Recommendations for Non-Adhesive Backed Printable Film & "Gripper": • Ideal for flat, horizontal surface counter mats and other P-O-P displays that do not require use of adhesive, foam or rubber backing • Not designed for use on floors as floor mats • FlexMark® 6120 is designed to be laminated to FlexMark® 6121 ("Gripper")  
View [How the System Works](#). \* 212°F (100°C) for 30 mins. † 212°F (100°C) for 30 mins.

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	6.6	

Test Method:

Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
--------------------	---------------	-------

Test Method:

Additional Properties	Value	Test Method
Expected Shear		
Tack		
Expected Exterior Life		
Additional Information		
Service Temperature		
Minimum Application Temperature		
Storage Stability		

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.