

Flexcon® FlexMark® OV6601 6.5 MIL CLEAR VELVET VINYL OVERLAMINATE

6.5 Mil Rigid Clear Velvet Overlaminate for indoor floor advertising. FLX019124

Benefits

• Velvet finish enhances graphic images, prevents glare

Features

- 6.2 mil velvet embossed rigid clear overlaminating vinyl film protects the printed graphic
- Adhesive bonds well to printed base film surfaces
- Adhesive offers excellent clarity and is designed to provide exceptional bond and excellent shear critical for durability under heavy foot traffic
- Permanent overlaminating pressure-sensitive acrylic adhesive bonds well to base film surface
- Backed with a 71 lb. smooth bleached white polycoated kraft release liner ideal for roll-form converting
- Smooth release liner provides improved adhesive clarity for vibrant graphics

Additional Details

FlexMark® OV6601 with FlexMark® Floor Art™ 4652,FlexMark® Floor Art™ 6610,or FlexMark® Floor Art™ 6640has been investigated by Underwriters Laboratories, Inc., and when used as a system, is in accordance with UL 410, the Standard for Floor Surfaces, for Floor-Graphic Materials (FGM). Please refer to Flexcon's Warranty & Limited Remedy Policy for Graphic Advertising for Floors and Indoor Carpets, and Application and Removal Instructions.Nothing contained herein shall expand the Floors and Indoor Carpets Limited Warranty or otherwise be construed as a warranty or guarantee.

Technical Data

Physical Properties

| Thickness (Mils [microns]) | Mils | Microns |
|----------------------------|-------|---------|
| Total Product | 12.45 | |

Test Method:



Flexcon® FlexMark® OV6601 6.5 MIL CLEAR VELVET VINYL OVERLAMINATE

6.5 Mil Rigid Clear Velvet Overlaminate for indoor floor advertising. FLX019124

| Adhesion Properties | | | | |
|---------------------------------|---------------|-------------|--|--|
| Ultimate Peel from | Average Oz/In | (N/m) | | |
| Test Method: | | | | |
| Additional Properties | Value | Test Method | | |
| Expected Shear (hours) | | | | |
| Tack (g) | | | | |
| Expected Exterior Life | | | | |
| Additional Information | | | | |
| Service Temperature | | | | |
| Minimum Application Temperature | | | | |
| Storage Stability | | | | |

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.