



# Flexcon® FlexMark® floor art™ 6640 4 MIL WHITE OPAQUE VINYL REM ADH LAYFLAT LINER (CARPET)

Indoor Carpet Advertising - White Opaque Base Film  
FLX019169

## Benefits

- UL Recognized

## Features

V 400 F WHITE OPAQUE A-120 94 PFW

- 3.5 mil white opaque vinyl provides excellent hiding power
- Excellent printability via UV and solvent screen, UV and solvent inkjet, UV offset, and latex
- Removable pressure-sensitive adhesive is designed to bond well to indoor low-pile commercial grade, stain resistant or non-stain resistant carpet
- 94 lb. premium grade moisture stable polycoated layflat release liner provides excellent stay flat release liner properties for printing and converting
- Ideal for sheetfed offset printing

## Additional Details

FlexMark® Floor Art™ 6640 with FlexMark® OV6601, FlexMark® OV6603BN, or FlexMark® OV6604 has been investigated by Underwriters Laboratories, Inc., and when used as a system, is in accordance with UL 410, the Standard for Floor Surfaces, for Floor-Graphic Materials (FGM).

Please refer to [Flexcon's Warranty & Limited Remedy Policy for Graphic Advertising for Floors and Indoor Carpets](#), and [Application and Removal Instructions](#). Nothing contained herein shall expand the Floors and Indoor Carpets Limited Warranty or otherwise be construed as a warranty or guarantee.

For Inkjet Printing:

- Typical max. ink limit = 250%
- When storing printed graphics, sheeted, stacked or in roll-form, consider leaving an unprinted margin (about 1/4") to allow for potential shrinkage of the film before trimming.

## Technical Data

### Physical Properties

| Thickness (Mils [microns]) | Mils  | Microns |
|----------------------------|-------|---------|
| Total Product              | 11.65 |         |

Test Method:



# Flexcon® FlexMark® floor art™ 6640 4 MIL WHITE OPAQUE VINYL REM ADH LAYFLAT LINER (CARPET)

Indoor Carpet Advertising - White Opaque Base Film  
FLX019169

## Adhesion Properties

| Ultimate Peel from | Average Oz/In | (N/m) |
|--------------------|---------------|-------|
|--------------------|---------------|-------|

Test Method:

| Additional Properties           | Value | Test Method |
|---------------------------------|-------|-------------|
| Expected Shear (hours)          |       |             |
| Tack (g)                        |       |             |
| Expected Exterior Life          |       |             |
| Additional Information          |       |             |
| Service Temperature             |       |             |
| Minimum Application Temperature |       |             |
| Storage Stability               |       |             |

## Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.