



Benefits

- Release liner has excellent moisture stability and is a good base for rotary, flatbed and steel rule diecutting
- Permanent acrylic adhesive offers high shear and excellent adhesion to metals, and high-surface energy plastics
- Performance, aggressive, permanent pressure-sensitive adhesive bonds well to a variety of surfaces

Features

- Pressure-sensitive transfer tape adhesives are the ideal solution for mounting and bonding because they transfer easily and bond well to many challenging surfaces.
- Applications Include: Nameplate/ Brand ID, Overlay, Decal, Sealing gaskets, Gap filling, Surface protection, Grip, traction and anti-slip, Noise and vibration control, Bonding films to replace rivets and weld.
- 4.0 mil transfer adhesive
- High-performance permanent acrylic adhesive bonds well to ABS, aluminum and stainless steel surfaces
- Backed with a 60 lb. bleached white kraft liner, polycoated and release coated on two sides
- Permanent acrylic pressure-sensitive adhesive bonds well to low- and high-surface energy plastics, painted metal, powder-coated paint, moderately rough surfaces. polycarbonate and fiberglass
- High-peel permanent acrylic adhesive resists cold flow and ooze

Additional Details

For the Complete Product Data View: [FLEXmount® L-344/V-344 Adhesive Series Data Sheet](#)

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	8.55	

Test Method:



Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
--------------------	---------------	-------

Test Method:

Additional Properties	Value	Test Method
Expected Shear (hours)		
Tack (g)		
Expected Exterior Life		
Additional Information		
Service Temperature		
Minimum Application Temperature		
Storage Stability		

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.