

Flexcon® FlexMark® V 400 F WHITE V-465 94 PRT PFW

Bumper Stickers White - Sheet Form FLX000005

Benefits

• In most cases, corona treatment is not required

Features

- Ideal for manual dispensing
- 3.5 mil flexible white vinyl provides good surface smoothness and conformability
- Print-receptive 4.0 mil white flexible vinyl provides consistent surface smoothness, excellent dimensional stability, and conformability
- Printable via thermal transfer, UV and solvent screen, UV, solvent & water flexo, and narrow-format UV inkjet
- Permanent pressure-sensitive acrylic adhesive bonds well to a variety of surfaces including paper, wood, glass and metal
- Backed with a 94 lb. premium grade liner with excellent layflat qualities and backside printability

Additional Details

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	10.75	
Film	3.5 +/- 10 %	89
Adhesive	0.7-0.8 +/- 0.1	18-20 +/- 3
Liner	6.7 +/- 10 %	170

Test Method: ASTM D 3652 (Modified for use with non-tape products)



Flexcon® FlexMark® V 400 F WHITE V-465 94 PRT PFW

Bumper Stickers White - Sheet Form FLX000005

Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
Glass	45	495
Painted Metal	43	473
Painted Wallboard	11	121
Painted Wood	11	121
Vinyl	41	451

Test Method: ASTM D 903 (Modified for 72 hour dwell time)

Additional Properties	Value	Test Method
Expected Shear (hours)	10	ASTM D 3654 Method A (1 hr. dwell, 1 sq. in, 4 lb. load)
Tack (g)	190	ASTM D 2979
Expected Exterior Life	Two Years	
Additional Information		
Service Temperature	-40°F to 176°F (-40°C to 80°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years stored at 70°F (21°C) and 50% relative humidity	

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.