

## **Benefits**

• Ideal for sheet-form converting

#### Features

- 3.25 mil flexible white vinyl film provides durability and easy installation
- Removable pressure-sensitive acrylic adhesive bonds well to a variety of surfaces including chrome-coated metal, chrome-coated plastic, glass, auto glass and painted plastic
- Backed with a layflat, sheet-form backside printable release liner for bumper sticker applications that require a coupon or promotional advertisement

# **Additional Details**

# **Technical Data**

#### **Physical Properties**

Thickness (Mils [microns])	Mils	Microns
Total Product	11.25	
Film	3.1 +/- 10 %	79
Adhesive	0.7-0.8 +/- 0.1 (3)	18-20
Liner	7.4 +/- 10 %	188

Test Method: ASTM D 3652 (Modified for use with non-tape products)



#### **Adhesion Properties**

Ultimate Peel from	Average Oz/In	(N/m)
Stainless Steel	33	363
Acrylic	46	506
Glass	30	330
Polypropylene	24	264

Test Method: ASTM D 903 (Modified for 72 hour dwell time)

Additional Properties	Value	Test Method		
Expected Shear (hours)	2	ASTM 3654 Method A (1 hr dwell, 1 sq. in, 4 lb. load)		
Tack (g)	350	ASTM D 2979		
Expected Exterior Life	Two years			
Additional Information	custom nature of this product, the o	Not to be used for setting specifications. Due to the custom nature of this product, the data presented are based on three or less production runs.		
Service Temperature	-40°F to 176°F (-40°C to 80°C)	-40°F to 176°F (-40°C to 80°C)		
Minimum Application Temperature	50°F (10°C)			
Storage Stability	Two years stored at 70°F (21°C) an	Two years stored at 70°F (21°C) and 50% RH		

### **Product Performance and Suitability**

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.