

Benefits

- Removable pressure-sensitive acrylic adhesive bonds well to metal, glass and high-surface energy plastics

Features

- 1.0 mil double-faced clear polyester film mounting film coated with a permanent pressure-sensitive acrylic adhesive on one side and a removable pressure-sensitive adhesive on the other side
- permanent adhesive bonds well to printed base film surfaces
- High-performance, permanent, pressure-sensitive acrylic adhesive bonds well to base film
- Adhesive offers excellent clarity and is designed to provide exceptional bond and excellent shear critical for durability under heavy foot traffic
- ultra-smooth blue polyester release liner ideal for roll-form converting

Additional Details

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	5.25	
Film	1.0 +/- 10%	25
Adhesive	0.9-1.0 +/- 0.1	25-28
Adhesive 2	0.7-0.8 +/- 0.1	18-20
Liner	1.0 +/- 5%	25
Liner 2	1.5 +/- 5%	38

Test Method: ASTM D 3652 (Modified for use with non-tape products)

Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
--------------------	---------------	-------

Test Method:

Additional Properties	Value	Test Method
Expected Shear (hours)		
Tack (g)		
Expected Exterior Life		
Additional Information		
Service Temperature		
Minimum Application Temperature		
Storage Stability		

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.