



# Flexcon® FlexMount® Select™ DF021621

Graphic Mounting Film: Clear Removable/Permanent with Double-Faced Release Liner  
FLX000547

## Benefits

- Ideal for roll-form and roll-to-sheet converting

## Features

- 0.5 mil double-faced clear polyester carrier film
- Clear removable pressure-sensitive acrylic adhesive on liner side, and an optically clear permanent pressure sensitive acrylic adhesive on the open side
- Backed with an 80 lb. double-faced release liner

## Additional Details

### Technical Data

#### Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	7.98	
Film	0.5 +/- 10%	13
Adhesive	Removable Adhesive 0.9-1.0 +/-	23-25
Adhesive 2	Permanent Adhesive 0.9-1.0 +/-	23-25
Liner	5.6 +/- 10%	142

Test Method: ASTM D 3652 (Modified for use with non-tape products)

**Adhesion Properties**

Ultimate Peel from	Average Oz/In	(N/m)
Acrylic (Perm)	35	385
Acrylic (Remove)	19	209
Glass (Perm)	25	275
Glass (Remove)	18	198
Polypropylene (Perm)	7	77

Test Method: ASTM D 903 (Modified for 72 hour dwell time)

Additional Properties	Value	Test Method
Expected Shear (hours)		
Tack (g)	Tack (gm/sq cm) 310 Tack (gm/sq cm) (PermanentAdhesive)660	ASTM D 2979
Expected Exterior Life	Depends on the substrate; both adhesives are suitable for outdoor use	
Additional Information	Room Temp (hours) (Permanent Adhesive) 100 Room Temp (hours) (RemovableAdhesive)Erratic shear caused by removable adhesive	
Service Temperature	-20°F to 302°F (-29°C to 150°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years stored at 70°F (21°C) and 50% RH	

## Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.