

Benefits

- CUL Recognized, L- Adhesives, UL Recognized

Features

- 1.0 mil matte clear overlaminating polyester resists temperature extremes, abrasion and chemical exposure for maximum label protection while reducing glare
- Permanent solvent-based acrylic biocompatible pressure-sensitive adhesive bonds well to low- and high-surface energy plastics, painted metal, powder-coated paint, polycarbonate and fiberglass without lifting
- Removable liner exposes adhesive to apply to your film/components
- 1 mil ultra smooth clear polyester release liner ensures optimum clarity

Additional Details

Technical Data

Physical Properties

| Thickness (Mils [microns]) | Mils | Microns |
|----------------------------|------|---------|
| Total Product | 2.79 | |

Test Method:

Adhesion Properties

| | | |
|--------------------|---------------|-------|
| Ultimate Peel from | Average Oz/In | (N/m) |
|--------------------|---------------|-------|

Test Method:

| Additional Properties | Value | Test Method |
|---------------------------------|-------|-------------|
| Expected Shear (hours) | | |
| Tack (g) | | |
| Expected Exterior Life | | |
| Additional Information | | |
| Service Temperature | | |
| Minimum Application Temperature | | |
| Storage Stability | | |

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.