



# Flexcon® Classics Plus® 41145

4.0 Mil White Vinyl, Permanent Adhesive Roll-Form Liner  
FLX059531

## Benefits

- UL-recognized under UL 969 - UL File No. PGGU2.MH10170 Marking and Labeling System Materials - Component
- cUL recognized under UL File No. PGGU8.MH10170 Marking and Labeling System Materials Certified for Canada - Component

## Features

- 3.5 mil flexible white vinyl provides good surface smoothness and conformability
- Film surface is compatible with most conventional and UV ink systems\*
- Versatile, general-purpose permanent pressure-sensitive acrylic adhesive bonds well to a variety of surfaces including low- and high-surface energy plastics
- Adhesive offers good tack and chemical resistance
- Backed with a 50 lb. bleached kraft release liner ideal for roll-form converting

## Additional Details

\*We recommend evaluating the ink system for compatibility with the product under the application conditions.

## Technical Data

### Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	7.75	
Film	3.5 +/- 10 %	89
Adhesive	0.75-0.85 +/- 0.1 (3)	19-21
Liner	3.1 +/- 10%	79

Test Method: ASTM D 3652 (Modified for use with non-tape product)

**Adhesion Properties**

Ultimate Peel from	Average Oz/In	(N/m)
Stainless Steel	67	737
Acrylic	80	880
Glass	70	770
Polypropylene	44	484

Test Method: ASTM D 903 (Modified for 72 hr. RT dwell time)

Additional Properties	Value	Test Method
Expected Shear (hours)	15	ASTM D 3654 Method A (1 hr. dwell, 1 sq. in, 4 lb. load)
Tack (g)	770	ASTM D 2979
Expected Exterior Life	Two Years	
Additional Information		
Service Temperature	-40°F to 176°F (-40°C to 80°C)	
Minimum Application Temperature	32°F (0°C)	
Storage Stability	Two years stored at 70°F (21°C) and 50% RH	

**Product Performance and Suitability**

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.