

Flexcon® Flex-Vu® OM 200 Clear A-324 100 Poly H-9R

Durable Goods and Equipment Labeling: Clear Polyester, Overlaminate FLX006068

Benefits

Features

- 2.0 mil clear polyester offers excellent clarity
- Removable pressure-sensitive adhesive
- Backed with an ultra smooth clear polyester release liner

Additional Details

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	3.74	

Test Method:



Flexcon® Flex-Vu® OM 200 Clear A-324 100 Poly H-9R

Durable Goods and Equipment Labeling: Clear Polyester, Overlaminate FLX006068

Adhesion				

Ultimate Peel from	Average Oz/In	(N/m)	

Test Method:

Additional Properties	Value	Test Method	
Expected Shear (hours)			
Tack (g)			
Expected Exterior Life			
Additional Information			
Service Temperature			
Minimum Application Temperature			
Storage Stability			

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.