

Flexcon® TamperMark™ MM 150 Silver Void TC-249 V-156 90 PFW

Silver Void Polyester FLX006234

Benefits

Ideal for sheet-form converting

Features

- 1.5 mil silver topcoated tamper-evident metallized polyester film
- Designed for applications requiring tamper evidence
- · Topcoat optimizes ink receptivity with most solvent and UV ink systems (please test for ink adhesion on your specific ink chemistry)
- High-adhesive bond onto plastic containers, cardboard, and packaging materials
- 90 lb. moisture stable polycoated layflat release liner ideal for sheet and roll-to-sheet converting

Additional Details

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	9.85	

Test Method:



Flexcon® TamperMark™ MM 150 Silver Void TC-249 V-156 90 PFW

Silver Void Polyester FLX006234

		D	
DΑ	hesion	Pro	nernes

Ultimate Peel from	Average Oz/In	(N/m)
Test Method:		
Additional Properties	Value	Test Method

Additional Properties	Value	Test Method			
Expected Shear (hours)	ted Shear (hours)				
Tack (g)					
Expected Exterior Life					
Additional Information					
Service Temperature					
Minimum Application Temperature					
Storage Stability					

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.