# Flexcon® OptiFlex® Reseal™ 20464

Topcoated 2.0 Mil Clear Polypropylene, Solvent-Free Resealable Adhesive, TracRite™ 120 Liner

FLX066713

## Benefits

- Performs reliably in freezer environments -20 o F (-29 o C)
- Adhesive complies with 21 CFR 175.125 for direct food contact
- Product has been 3rd party tested for High Pressure Processing (HPP) and adhesive was found to have the necessary strength and compatibility to withstand the HPP conditions

## Features

- 2.0 mil clear polypropylene offers excellent resistance to shrinkage, moisture, humidity and product contents
- Film offers excellent tear resistance and durability for opening and reclosure of flexible packaging substrates
- Printable via UV, solvent & water flexo, narrow-format UV inkjet, roll-form dry toner, UV rotary screen, UV letterpress and hot stamping.
- Resealable pressure-sensitive acrylic adhesive bonds well to low- and high- surface energy laminated flexible packaging substrates with clean, quiet and consistent reclosure
- Adhesive offers excellent clarity and wet out characteristics
- Polyester release liner for excellent on-press performance for tight-registration graphics & contains up to 60% post industrial recycled content

## Additional Details

## Technical Data

**Physical Properties**

| Thickness (Mils [microns]) | Mils | Microns |
|---|---|---|
| Total Product | 4.3 | |

Test Method:

**Adhesion Properties**

| Ultimate Peel from | Average Oz/In | (N/m) |
|---|---|---|

Test Method:

| Additional Properties | Value | Test Method |
|---|---|---|
| Expected Shear (hours) | | |
| Tack (g) | | |
| Expected Exterior Life | | |
| Additional Information | | |
| Service Temperature | | |
| Minimum Application Temperature | | |
| Storage Stability | | |

## Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.

© 2026 Flexcon, Inc. All rights reserved.