



# Flexcon® PharmCal® PP 400 White Opaque MTC-135 V-344DL Special 50K-8 Remoisturize

Pharmaceutical Pressure-Sensitive Labeling Solutions  
FLX066757

## Benefits

- High peel, high shear adhesive resists cold flow and oozing, gaining efficiencies in diecutting and dispensing
- Backed with a 50 lb. bleached kraft release liner ideal for roll-form converting
- 6-month change notification

## Features

- Matte topcoated 4.0 mil white polypropylene (vinyl alternative) provides consistent surface smoothness and excellent dimensional stability
- Product can be applied at low temperatures

## Additional Details

### Technical Data

#### Physical Properties

| Thickness (Mils [microns]) | Mils | Microns |
|----------------------------|------|---------|
| Total Product              | 8.44 |         |

Test Method:



# Flexcon® PharmCal® PP 400 White Opaque MTC-135 V-344DL Special 50K-8 Remoisturize

Pharmaceutical Pressure-Sensitive Labeling Solutions  
FLX066757

## Adhesion Properties

| Ultimate Peel from | Average Oz/In | (N/m) |
|--------------------|---------------|-------|
|--------------------|---------------|-------|

Test Method:

| Additional Properties           | Value | Test Method |
|---------------------------------|-------|-------------|
| Expected Shear (hours)          |       |             |
| Tack (g)                        |       |             |
| Expected Exterior Life          |       |             |
| Additional Information          |       |             |
| Service Temperature             |       |             |
| Minimum Application Temperature |       |             |
| Storage Stability               |       |             |

## Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.