

# Flexcon® DermaFlex™ NNRU 100 Clear H-506 Spec 50K-8

Skin Contact Applications: Clear Nylon Reinforced Polyurethane Film with H-506 FLX068278

### **Benefits**

DermaFlex™ adhesives have been tested for biocompatibility (skin irritation, sensitization, and cytotoxicity) by Flexcon's adhesive suppliers using ISO-10993 or similar test methods\*

## **Features**

- NNRU (Nylon Netting Reinforced Urethane) substrate consisting of a conformable polyurethane film reinforced with a nylon netting for high extensibility & strength
- .001" clear nylon reinforced polyurethane film
- Gentle release acrylic adhesive bonds well, yet removes gently from skin
- Backed with a 50 lb. bleached kraft release liner ideal for roll-form converting

### **Additional Details**

Please note: Our combination of flexible substrates and skin-friendly adhesives form a product portfolio that is suitable for a variety of applications. Choose from existing products, or work with our Technical Service team to create your own unique combination that's optimized for your specific application needs \*Biocompatibility testing was completed using a similar 'source' adhesive in some circumstances. Full biocompatibility results are available on the web and upon request.

For guidance only, not to be used for setting specifications. The data presented are based on three or less production runs. Product data sheets are updated as necessary, without notice. Please contact Flexcon to request a copy of most recent version.

DISCLAIMER: FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE. This product is a device component intended solely for further processing, manufacturing, or incorporation into a finished device, and is further intended only for use as a device component on intact skin (i.e., not intended for use in the presence of open sores or wounds nor for applications inside the body). Customer is solely responsible for determining whether this component product is fit for Customer's intended use, including, without limitation, incorporation into Customer's finished device(s), and for performing any additional testing that may be necessary to support Customer's intended use. Customer is solely responsible for ensuring that its use of the component product is in compliance with the applicable laws and for obtaining any necessary clearances or approvals from its use of the component product and any finished device that incorporates the component product.

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon. Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated.

## **Technical Data**

#### **Physical Properties**

Thickness (Mils [microns])	Mils	Microns
Total Product	14.24	
Film	1.0 +/- 10%	25
Adhesive	3.8-4.2 +/- 0.4	97-107 +/- 10
Liner	3.1 +/- 10 %	79

Test Method: ASTM D 3652 (Modified for use with non-tape products)



# Flexcon® DermaFlex™ NNRU 100 Clear H-506 Spec 50K-8

Skin Contact Applications: Clear Nylon Reinforced Polyurethane Film with H-506 FLX068278

#### **Adhesion Properties**

Ultimate Peel from	Average Oz/In	(N/m)
Acrylic	3	33
Glass	3	33
Polyethylene	2	22
Polypropylene	2	22
Stainless Steel	3	33

Test Method: ASTM D 903 (Modified for 72 hour dwell time)

Additional Properties	Value	Test Method
Expected Shear (hours)	Less than 0.25	ASTM D 3654 Method Aa. 1 hr. dwellb. 1 sq. in. surfacec. 4 lb. load
Tack (g)	70	ASTM D 2979
Expected Exterior Life	N/A	
Additional Information		
Service Temperature	N/A	
Minimum Application Temperature	N/A	
Storage Stability	Two years stored at 70°F (21°C) and 50% relative humidity	

# **Product Performance and Suitability**

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.