



Flexcon® PharmCal® Supreme 069045 (PharmCal® PM 150 Clear TC-716 V-95 TracRite™ 150)

1.5 Mil Clear Polyester, Permanent Adhesive, Poly Liner
FLX069045

Benefits

- Excellent performance in autoclave or pasteurization
- 6-month change notification

Features

- 1.5 mil clear polyester offers excellent resistance to shrinkage, high temperatures, moisture, humidity and product contents
- Topcoat optimizes printability with UV & solvent screen, flexographic, narrow-format UV inkjet, and hot stamping
- Permanent pressure-sensitive acrylic adhesive bonds well to glass and polypropylene
- Adhesive offers excellent tack, clarity and wet out characteristics
- Flexcon® TracRite™ 150 polyester release liner for excellent on-press performance for tight registration graphics
- Release liner is ideal for roll-form applications that require high-speed dispensing

Additional Details

"Fit-for-use" testing is recommended under actual application conditions

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	3.85	
Film	1.4 +/- 10%	36
Adhesive	0.6-0.7 +/- 0.1 (3)	15-18
Liner	1.4 +/- 5%	36

Test Method: ASTM D 3652 (Modified for use with non-tape products)



Flexcon® PharmCal® Supreme 069045 (PharmCal® PM 150 Clear TC-716 V-95 TracRite™ 150)

1.5 Mil Clear Polyester, Permanent Adhesive, Poly Liner
FLX069045

Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
Glass	50	550
Polypropylene	4	44

Test Method: ASTM D 903 (Modified for 72 hour dwell time)

Additional Properties	Value	Test Method
Expected Shear (hours)		
Tack (g)	510	ASTM D 2979
Expected Exterior Life	Indoor use only	
Additional Information		
Service Temperature	-40°F to 302°F (-40°C to 150°C)	
Minimum Application Temperature	35°F (1.7°C)	
Storage Stability	Two years stored at 70°F (21°C) and 50% RH	

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.