

Flexcon® OptiFlex® EcoFocus® PP 230 H WHITE TC-458 V-52RE SPEC 40K-8

2.3 mil hard white polypropylene with wash-off adhesive enabling the recycling of PET container FLX069991

Benefits

- Product has been 3rd party tested for Higher Pressure Processing (HPP) and adhesive was found to have the necessary strength and compatibility to withstand the HPP conditions
- APR Critical Guidance Recognition Flexcon's undecorated OptiFlex® EcoFocus® PP 230 H White TC pressure-sensitive labels, with V-52RE adhesive
 meet or exceed APR's Critical Guidance Protocol for Clear PET Articles with Labels and Closures

Features

- Topcoated 2.3 mil hard white polypropylene (BOPP) offers excellent resistance to shrinkage, moisture, humidity and product contents
- High-performance adhesive adheres well to PET containers
- Adhesive separates cleanly from PET flake during the recycling process allowing for the collection of rPET
- Printable via UV, solvent & water flexo, narrow-format UV inkjet, roll-form dry toner, UV rotary screen, UV letterpress and hot stamping

Additional Details

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	5.75	

Test Method:



Flexcon® OptiFlex® EcoFocus® PP 230 H WHITE TC-458 V-52RE SPEC 40K-8

 $2.3 \, \mathrm{mil}$ hard white polypropylene with wash-off adhesive enabling the recycling of PET container FLX069991

Adhesion Properties				
Ultimate Peel from	Average Oz/In	(N/m)		
Test Method:				
Additional Properties	Value	Test Method		
Expected Shear (hours)				
Tack (g)				
Expected Exterior Life				
Additional Information				
Service Temperature				
Minimum Application Temperature				
Storage Stability				

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.