



# Flexcon® ThermlFilm® HT™ 9000V2

2.0 mil high temperature white polyimide film  
FLX070418

## Benefits

- 2 mil (50 micron) high temperature white polyimide film, topcoated for extensive printability
- Withstands intermittent heat up to 750°F (399°C) for high-heat applications
- 600 DPI resolution for sharp barcodes, data matrix codes, and alphanumeric tracking
- ANSI scannability compliance ensures reliable long-term traceability
- Chemical, solvent, and abrasion resistance (OHR1 Compliant) for harsh industrial conditions
- Low-outgassing adhesive for sensitive applications
- UL 969 recognized, REACH & RoHS compliant, and halogen-free

## Features

## Additional Details

## Technical Data

### Physical Properties

Thickness (Mils [microns])	Mils	Microns
----------------------------	------	---------

Test Method:



# Flexcon® ThermoFilm® HT™ 9000V2

2.0 mil high temperature white polyimide film  
FLX070418

## Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
--------------------	---------------	-------

Test Method:

Additional Properties	Value	Test Method
Expected Shear (hours)		
Tack (g)		
Expected Exterior Life		
Additional Information		
Service Temperature		
Minimum Application Temperature		
Storage Stability		

## Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.