



Flexcon® Classics Plus® Select™ 31086SL

3.1 Mil White Vinyl, Acrylic Adhesive, Sheet-Form Liner
FLX009648

Benefits

Features

- 3.1 flexible white vinyl film provides durability and easy installation
- General-purpose emulsion acrylic adhesive used for both permanent and removable applications. Adhesive bonds well to a variety of surfaces including chrome-coated metal, chrome-coated plastic, glass, auto glass and painted plastic
- 90 lb. moisture stable polycoated layflat release liner ideal for sheet and roll-to-sheet converting
- Excellent layflat release liner properties for printing and converting
- Ideal for manual dispensing

Additional Details

Technical Data

Physical Properties

Thickness (Mils [microns])	Mils	Microns
Total Product	10.7	
Film	3.1 +/-10%	79
Adhesive	0.75-0.85 +/-0.1	19-21 +/- 3
Liner	6.9 +/- 10%	175

Test Method: ASTM D 3652 (Modified for use with non-tape product)



Flexcon® Classics Plus® Select™ 31086SL

3.1 Mil White Vinyl, Acrylic Adhesive, Sheet-Form Liner
FLX009648

Adhesion Properties

Ultimate Peel from	Average Oz/In	(N/m)
Automotive Glass	36	396
Chrome-Coated Metal	44	484
Chrome-Coated Plastic	46	506
Glass	30	330
Painted Plastic	46	506

Test Method: ASTM D 903 (Modified for 72 hr. dwell time)

Additional Properties	Value	Test Method
Expected Shear	2	ASTM D 3654 Method A (1 hr dwell, 1 sq. in, 4 lb. load)
Tack	350	ASTM D 2979
Expected Exterior Life	Two years	
Additional Information		
Service Temperature	-40°F to 176°F (-40°C to 80°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years stored at 70°F (21°C) and 50% relative humidity	

Product Performance and Suitability

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesman, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.