



SOLUTIONS FOR FLOOR, CARPET, & OUTDOOR WALKWAY GRAPHICS

	FLX #	FLEXcon® Product (Meets industry slip standard when base film and overlaminate are used as a system)	Print Method					Availability							
			Screen		Inkjet		Offset	HP Latex	Flexo		Sample		Shipment		
			UV	Solvent	UV	Solvent	UV		UV	Water	Sheets	Rolls	Same Day ²	Quick-Ship (2 day) ◆	
Most Popular		<i>Approved Base Films for Indoor Floors - (Commercial PVC, Ceramic Tile-some, Sealed Concrete, & Linoleum)</i>													
	059983	FLEXmark® CR (clear)	•	•	•	•	•	•			•	•	•	•	
	059985	FLEXmark® WR (white)	•	•	•	•	•	•			•	•	•	•	
	064832	NEW! FLEXmark® WRAE (white with air egress liner)	•	•	•	•	•	•			•	•	•	•	
	019141	FLEXmark® floor art™ 6610 (white opaque)	•	•	•	•	•				•	•	•	•	
	068691	FLEXmark® floor art™ 6610TF† (white opaque)		•		•				•	•			•	
	025166	FLEXmark® floor art™ 4652 (white)	•	•	•	•	•	•			•	•		•	
		<i>Approved Overlaminates for Indoor Floors</i>													
	019124	FLEXmark® OV6601 (650 rigid clear velvet) <i>For use with base film: FLEXmark® floor art™ 4652 and 6610</i>		•		•						•	•	•	•
	066159	FLEXmark® OV6603BN (600 frosty clear safari) <i>For use with base film: FLEXmark® floor art™ 4652 and 6610</i>		•		•						•	•	•	•
059980	FLEXmark® CP (clear) <i>For use with base film: FLEXmark® CR, WR, and WRAE</i>		•		•						•	•	•	•	
019129	FLEXmark® OV6602 (4 hard clear) <i>For use with base film: FLEXmark® CR, WR and WRAE; FLEXmark® floor art™ 4652, 6610, and 6610TF</i>		•		•						•		•	•	
Specialty		<i>Approved Base Film for Indoor Floors (Large-Paneled Graphics) - (Commercial PVC, Ceramic Tile-some, & Sealed Concrete)</i>													
	063182	FLEXmark® floor art™ 4730 (white opaque)	•	•	•	•	•	•	•	•	•	•	•	•	
		<i>Approved Textured Overlaminates for Indoor Floors (Large-Paneled Graphics)</i>													
	066234	FLEXmark® OV1450 (14.5 clear matte textured)		•		•					•	•	•	•	



SOLUTIONS FOR FLOOR, CARPET, & OUTDOOR WALKWAY GRAPHICS

		Print Method					Availability											
		Screen		Inkjet		Offset	HP Latex	Flexo		Sample		Shipment						
FLX #		FLEXcon® Product (Meets industry slip standard when base film and overlaminate are used as a system)					UV	Solvent	UV	Solvent	UV	HP Latex	UV	Water	Sheets	Rolls	Same Day ²	Quick-Ship (2 day) ◆
Carpet		<i>Approved Base Film for Indoor Carpets - (Low Pile Carpet)</i>																
	019169	FLEXmark® floor art™ 6640 (white opaque)					●	●	●	●	●		●				●	●
		<i>Approved Overlaminates</i>																
	019124	FLEXmark® OV6601 (650 rigid clear velvet)													●	●	●	●
	066159	FLEXmark® OV6603BN (600 frosty clear safari)													●	●	●	●
	024305	FLEXmark® OV6604 (2300 clear safari)													●	●		●
Outdoor Walkway		<i>Approved Base Film for Outdoor Walkways - (Sealed & Unsealed Concrete)</i>																
	068648	FLEXmark® floor art™ 6650 (white opaque)					●	●	●	●	●		●		●	●	●	●
		<i>Approved Overlamine for Outdoor Walkways</i>																
	066234	FLEXmark® OV1450 (14.5 clear matte textured)													●	●	●	●

†For offline laminating, FLEXmark® OV6601 and FLEXmark® OV6603BN can be used with FLEXmark® floor art™ 6610TF.

4/27/2021

◆ Quick-Ship: product is stocked in wide web.

²Pre-Slit rolls ship same day when order is placed by 2 PM Monday - Friday in the time zone of the shipping location.

Some base films have topcoated versions available.

For pricing and availability, go to www.FLEXcon.com and log onto My FLEXcon Info.



All product combinations, as listed above, are UL 410 classified. Any deviations from the above combinations are not recommended nor warranted by FLEXcon, including, but not limited to: other base film and overlaminate combinations, nor FLEXcon base films or overlaminates used with another supplier's base films or overlaminates. FLEXmark® floor art™ 6650 and FLEXmark® OV1450 when used as a system is also DIN 51130 certified.

~ The typical performance data and recommendations for using FLEXcon products shall be used only as a guide. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for its intended use. ~